

TECHNICAL DATA SHEET

DESCRIPTION

General purpose biaxially-oriented polypropylene (BOPP) film, reinforced with fiberglass, manufactured with hot melt adhesive.

Superior strength and bonds instantly when minimum pressure is applied. Ultra strong tensile strength and easy unwind ensure consistent, reliable seals to a variety of corrugated, plastics and metals.

PRODUCT APPLICATION

- Heavy weight box sealing
- Used for bundling and strapping, pipes, tubes, pallets, etc.
- Great temperature range and holding power

FEATURES

- Smooth, easy release from tape dispenser
- Ultra strong & durable polypropylene



FT-6602

Industrial Grade

Adhesion to Steel (ASTM 3330)	52 oz/in (59 N/100 mm)
Tensile (Machine) (ASTM D3759)	170 lbs
Tensile (Cross) (ASTM D3759)	N/A
Elongation (ASTM D3759)	7%
Total Thickness	5.50 mil
Adhesive	Hot Melt
Application Range	32 F to 120 F
Colors	Clear with Filament
Sizes (Width)	1/8 to 3-inch
Sizes (Length)	60 yards
Storage	40 F to 80 F 40% to 55% Humidity
Shelf Life	24 months

NOMINAL VALUES

The following data are nominal values based on ASTM. This data may vary slightly from roll to roll. The values below have been created using averaged testing samples. We recommend the user test the product for their application, in their environment, to ensure 100% compliance.



A Universal Company

16 Stenersen Lane Suite 4B | Hunt Valley, MD 21030
www.IncrediSeal.com | Sales@IncrediSeal.com
Customer Service: (888) 496-2747